

EUROLUB GEAR FLUIDE II D

Description

ATF for use in automatic transmissions, power steering systems, torque converters and drivetrains in passenger cars, commercial vehicles and machinery:

- Good wear protection
- Long transmission service life
- Good temperature stability
- Optimised oxidation stability

Colour: red

Can be used with

GM Dexron II D
MB 236.6
DTFR 13C140
MAN 339 Typ Z1 / V1
Allison C-4
CAT TO-2
Voith 55.6335 (G607)
ZF TE-ML 03D/04D/11A/14A/17C
BMW 81 22 9 400 272
Ford M2C-138CJ
GM 90350342
MB 000 989 92 03
Opel 19 40 700
Vauxhall 90350342
Volvo 1161744

Delivery

Art.-No. 373001	12 x 1 Liter	can
Art.-No. 373020	20 Liter	can
Art.-No. 373060	60 Liter	drum
Art.-No. 373208	208 Liter	drum
Art.-No. 373100	Container	800 – 3.000 litre
Art.-No. 373000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.870
Viscosity at 40°C	mm ² /s	DIN 51 562	34.9
Viscosity at 100°C	mm ² /s	DIN 51 562	6.8
Viscosityindex (VI)	-	DIN ISO 2909	156
Flash point (COC)	°C	DIN ISO 2592	166
Pourpoint	°C	DIN ISO 3016	-45

Product Information

