

EUROLUB ZH-L ST HYDRAULIK-FLUID

Description

ZH-L ST HYDRAULIC FLUID is a special hydraulic fluid based on base oils combined with specially formulated additives. This special hydraulic fluid is used in a wide variety of hydraulic systems, such as power steering systems, level control systems, hydropneumatic suspension, shock absorbers, hydrostatic drives, ABS/ASR and ASC systems, and electrohydraulic folding roof control systems.

Appearance: green

Can be used with

VW TL 52146 (G 002 000/G 004 000)
DTFR 31B120 (345.0)
BMW 812 29 407 758
Ford WSS-M2C204-A
GM/Opel B040 0070
Fendt X 902.011.622
MAN M 3289

Audi G 004 000 M2
BMW 83 29 0 429 576
Chrysler MS 11655b
Citroen 9979.A3
DAF 1786 432
Fiat 9.55550-AG3
Ford 1 384 110
GM 93160548
Hyundai 00232-19017
Land Rover LR 003401
MAN 9.110.030.427
Mini (BMW) 83 29 0 429 576
Opel 19 40 715
Porsche 000 043 204 89
Saab 93 160 548
Seat G 004 000 M2
Skoda G 004 000 M2
Vauxhall 93160548
Volvo 30741424
VW G 004 000 M2

Delivery

Art.-No. 564001	12 x 1 Liter	bottle
Art.-No. 564020	20 Liter	can
Art.-No. 564060	60 Liter	drum
Art.-No. 564208	208 Liter	drum
Art.-No. 564100	Container	800 – 3.000 litre
Art.-No. 564000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.830
Viscosity at 40°C	mm ² /s	DIN 51 562	19.9
Viscosity at 100°C	mm ² /s	DIN 51 562	6.2
Viscosityindex (VI)	-	DIN ISO 2909	304
Flash point (COC)	°C	DIN ISO 2592	216
Pourpoint	°C	DIN ISO 3016	-51