

EUROLUB GEAR AXLE SB 75W-90

Description

GEAR AXLE SB 75W-90 is suitable for very high mechanical and thermal loads, even at longer service intervals.

Can be used with

API GL-4/GL-5/MT-1
MIL-L-2105D/MIL-PRF-2105E, SAE J2360
DTFR 12B140
MAN 341 Typ Z2
MAN 342 Typ S1
SCANIA STO 1:0
Volvo 97312
ZF TE-ML 02B/05A/12L/12N/16F/17B/19C/21A
Meritor 076-N
EATON Europe

Delivery

Art.-No. 347020	20 Liter	can
Art.-No. 347060	60 Liter	drum
Art.-No. 347208	208 Liter	drum
Art.-No. 347100	Container	800 – 3.000 litre
Art.-No. 347000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.890
Viscosity at 40°C	mm ² /s	DIN 51 562	74.6
Viscosity at 100°C	mm ² /s	DIN 51 562	14.9
Viscosityindex (VI)	-	DIN ISO 2909	211
Flash point (COC)	°C	DIN ISO 2592	216
Pourpoint	°C	DIN ISO 3016	-45